









POWERFULL S - 30 to 80 kva




Standard Electricity Generator - POWERFULL series S version with PERKINS Diesel Engine water-cooled
1500 rpm - 50 Hz and MARELLI Alternator at 400/230 Volt - three-phases with neutral

| Mod. | | Power | | | | Engine Mod. | Alternator Mod. |
|---|--------|--------|-------|--------|-------|----------------|--------------------|
| | | P.R.P. | | L.T.P. | | | |
| | | kVA | kW | kVA | kW | | |
|  | P 30 S | 30,00 | 24,00 | 33,00 | 26,40 | 1103A-33G | MJB160MB4 |
|  | P 41 S | 42,00 | 33,60 | 46,00 | 36,80 | 1103A-33TG1 | MJB200SA4 |
|  | P 65 S | 60,00 | 48,00 | 66,00 | 52,80 | 1103A-33TG2 | MJB200MA4 |
|  | P 80 S | 80,00 | 64,00 | 88,00 | 70,40 | 1104A-44TG2 | MJB225SA4 |




Standard Electricity Generator - POWERFULL series S version with PERKINS Diesel Engine water-cooled
1500 rpm - 50 Hz and STAMFORD Alternator at 400/230 Volt - three-phases with neutral

| Mod. | | Power | | | | Engine Mod. | Alternator Mod. |
|---|--------|--------|-------|--------|-------|----------------|--------------------|
| | | P.R.P. | | L.T.P. | | | |
| | | kVA | kW | kVA | kW | | |
|  | P 30 S | 30,00 | 24,00 | 33,00 | 26,40 | 1103A-33G | PI144G |
|  | P 41 S | 40,00 | 32,00 | 45,00 | 36,00 | 1103A-33TG1 | PI144J |
|  | P 65 S | 60,00 | 48,00 | 63,00 | 50,40 | 1103A-33TG2 | UCI224E |
|  | P 80 S | 80,00 | 64,00 | 88,00 | 70,40 | 1104A-44TG2 | UCI224G |

Standard Electricity Generator - POWERFULL series S version with JOHN DEERE Diesel Engine water-cooled
1500 rpm - 50 Hz and MARELLI Alternator at 400/230 Volt - three-phases with neutral

| Mod. | | Power | | | | Engine Mod. | Alternator Mod. |
|---|---------|--------|-------|--------|-------|----------------|--------------------|
| | | P.R.P. | | L.T.P. | | | |
| | | kVA | kW | kVA | kW | | |
|  | JD 30 S | 30,00 | 24,00 | 33,00 | 26,40 | 3029DF128 | MJB160MB4 |
|  | JD 61 S | 60,00 | 48,00 | 68,00 | 54,40 | 4045TFU70 | MJB200MA4 |
|  | JD 80 S | 80,00 | 64,00 | 88,00 | 70,40 | 4045TF258 | MJB225SA4 |

Standard Electricity Generator - POWERFULL series S version with JOHN DEERE Diesel Engine water-cooled
1500 rpm - 50 Hz and STAMFORD Alternator at 400/230 Volt - three-phases with neutral

| Mod. | | Power | | | | Engine Mod. | Alternator Mod. |
|---|---------|--------|-------|--------|-------|----------------|--------------------|
| | | P.R.P. | | L.T.P. | | | |
| | | kVA | kW | kVA | kW | | |
|  | JD 30 S | 30,00 | 24,00 | 33,00 | 26,40 | 3029DF128 | PI144G |
|  | JD 61 S | 60,00 | 48,00 | 63,00 | 50,40 | 4045TFU70 | UCI224E |
|  | JD 80 S | 80,00 | 64,00 | 88,00 | 70,40 | 4045TF258 | UCI224G |