







## Gen Sets 50 Hz 400 Volt Version SS from 110 kVA to 400 kVA








Standard Electricity Generator - POWERFULL series SS version with PERKINS Diesel Engine water-cooled 1500 rpm - 50 Hz and MARELLI Alternator at 400/230 Volt - three-phases with neutral

Mod.		Power				Engine	Alternator
		P.R.P.		L.T.P.		Mod.	Mod.
		kVA	kW	kVA	kW		
	P 130 SS	132,00	105,60	145,00	116,00	1006TAG	MJB225LA4
	P 155 SS	150,00	120,00	166,00	132,80	1006TAG2	MJB250MA4
	P 180 SS	180,00	144,00	200,00	160,00	1106C-E66TAG4	MJB250MB4

Standard Electricity Generator - POWERFULL series SS version with PERKINS Diesel Engine water-cooled 1500 rpm - 50 Hz and STAMFORD Alternator at 400/230 Volt - three-phases with neutral








Mod.		Power				Engine	Alternator
		P.R.P.		L.T.P.		Mod.	Mod.
		kVA	kW	kVA	kW		
	P 130 SS	136,00	108,80	150,00	120,00	1006TAG	UCI274E
	P 155 SS	150,00	120,00	166,00	132,80	1006TAG2	UCI274F
	P 180 SS	180,00	144,00	194,00	155,20	1106C-E66TAG4	UCI274G

Standard Electricity Generator - POWERFULL series SS version with JOHN DEERE Diesel Engine water-cooled 1500 rpm - 50 Hz and MARELLI Alternator at 400/230 Volt - three-phases with neutral


Mod.		Power				Engine	Alternator
		P.R.P.		L.T.P.		Mod.	Mod.
		kVA	kW	kVA	kW		
	JD 120 SS	120,00	96,00	132,00	105,60	6068TF258	MJB225LA4
	JD 151 SS	165,00	132,00	180,00	144,00	6068HF258	MJB250MA4
	JD 180 SS	180,00	144,00	198,00	158,40	6068HF258	MJB250MB4
	JD 200 SS	220,00	176,00	240,00	192,00	6081HF001-250	MJB250LA4
	JD 250 SS	250,00	200,00	275,00	220,00	6081HF001-250	MJB250LB4
	JD 251 SS	255,00	204,00	300,00	240,00	6081HF001-250	MJB315SA4
	JD 400 SS	388,00	310,40	429,00	343,20	6125HF070	MJB315MA4

Standard Electricity Generator - POWERFULL series SS version with JOHN DEERE Diesel Engine water-cooled 1500 rpm - 50 Hz and STAMFORD Alternator at 400/230 Volt - three-phases with neutral


Mod.		Power				Engine	Alternator
		P.R.P.		L.T.P.		Mod.	Mod.
		kVA	kW	kVA	kW		

	JD 120 SS	120,00	96,00	130,00	104,00	6068TF258	UCI274D
	JD 151 SS	160,00	128,00	175,00	140,00	6068HF258	UCI274F
	JD 180 SS	180,00	144,00	194,00	155,20	6068HF258	UCI274G
	JD 200 SS	200,00	160,00	220,00	176,00	6081HF001-250	UCI274H
	JD 250 SS	250,00	200,00	275,00	220,00	6081HF001-250	UCDI274K
	JD 251 SS	255,00	204,00	300,00	240,00	6081HF001-250	HCI4D
	JD 400 SS	388,00	310,40	429,00	343,20	6125HF070	HCI4F

Standard Electricity Generator - POWERFULL series SS version with VOLVO-PENTA Diesel Engine water-cooled 1500 rpm - 50 Hz and MARELLI Alternator at 400/230 Volt - three-phases with neutral

Mod.	Power				Engine	Alternator	
	P.R.P.		L.T.P.				
	kVA	kW	kVA	kW	Mod.	Mod.	
	V 326 SS	326,00	260,80	358,00	286,40	TAD941GE	MJB315SB4

Standard Electricity Generator - POWERFULL series SS version with VOLVO-PENTA Diesel Engine water-cooled 1500 rpm - 50 Hz and STAMFORD Alternator at 400/230 Volt - three-phases with neutral

Mod.	Power				Engine	Alternator	
	P.R.P.		L.T.P.				
	kVA	kW	kVA	kW	Mod.	Mod.	
	V 326 SS	326,00	260,80	358,00	286,40	TAD941GE	HCI4E