

PRODUCTS - POWERFULL SILENT - POWERFULL C - 100 to 180 kva

Standard Electricity Generator - POWERFULL series C version with PERKINS Diesel Engine water-cooled 1500 rpm - 50 Hz and MARELLI Alternator at 400/230 Volt - three-phases with neutral

Mod.	Power				Engine Mod.	Alternator Mod.
	P.R.P.		L.T.P.			
	kVA	kW	kVA	kW		
 P 105 C	100,00	80,00	110,00	88,00	1104C-44TAG2	MJB225MA4
 P 130 C	132,00	105,60	145,00	116,00	1006TAG	MJB225LA4
 P 155 C	150,00	120,00	166,00	132,80	1006TAG2	MJB250MA4
 P 180 C	180,00	144,00	200,00	160,00	1106C-E66TAG4	MJB250MB4

Standard Electricity Generator - POWERFULL series C version with PERKINS Diesel Engine water-cooled 1500 rpm - 50 Hz and STAMFORD Alternator at 400/230 Volt - three-phases with neutral

Mod.	Power				Engine Mod.	Alternator Mod.
	P.R.P.		L.T.P.			
	kVA	kW	kVA	kW		
 P 105 C	100,00	80,00	110,00	88,00	1104C-44TAG2	UCI274C
 P 130 C	136,00	108,80	150,00	120,00	1006TAG	UCI274E
 P 155 C	150,00	120,00	166,00	132,80	1006TAG2	UCI274F
 P 180 C	180,00	144,00	194,00	155,20	1106C-E66TAG4	UCI274G

Standard Electricity Generator - POWERFULL series C version with JOHN DEERE Diesel Engine water-cooled 1500 rpm - 50 Hz and MARELLI Alternator at 400/230 Volt - three-phases with neutral

Mod.	Power				Engine Mod.	Alternator Mod.
	P.R.P.		L.T.P.			
	kVA	kW	kVA	kW		
 JD 100 C	100,00	80,00	110,00	88,00	4045HF158	MJB225MA4
 JD 120 C	120,00	96,00	132,00	105,60	6068TF258	MJB225LA4
 JD 151 C	165,00	132,00	180,00	144,00	6068HF258	MJB250MA4
 JD 180 C	180,00	144,00	198,00	158,40	6068HF258	MJB250MB4

Standard Electricity Generator - POWERFULL series C version with JOHN DEERE Diesel Engine water-cooled 1500 rpm - 50 Hz and STAMFORD Alternator at 400/230 Volt - three-phases with neutral

Mod.	Power				Engine Mod.	Alternator Mod.
	P.R.P.		L.T.P.			
	kVA	kW	kVA	kW		
 JD 100 C	100,00	80,00	110,00	88,00	4045HF158	UCI274C
 JD 120 C	120,00	96,00	130,00	104,00	6068TF258	UCI274D

	JD 151 C	160,00	128,00	175,00	140,00	6068HF258	UC1274F
	JD 180 C	180,00	144,00	194,00	155,20	6068HF258	UC1274G

Standard Electricity Generator - POWERFULL series C version with DEUTZ Diesel Engine water-cooled 1500 rpm - 50 Hz and MARELLI Alternator at 400/230 Volt - three-phases with neutral

Mod.	Power				Engine	Alternator	
	P.R.P.		L.T.P.				
	kVA	kW	kVA	kW	Mod.	Mod.	
	D 100 C	105,00	84,00	111,00	88,80	BF4M1013EC	MJB225MA4

Standard Electricity Generator - POWERFULL series C version with DEUTZ Diesel Engine water-cooled 1500 rpm - 50 Hz and STAMFORD Alternator at 400/230 Volt - three-phases with neutral

Mod.	Power				Engine	Alternator	
	P.R.P.		L.T.P.				
	kVA	kW	kVA	kW	Mod.	Mod.	
	D 100 C	100,00	80,00	110,00	88,00	BF4M1013EC	UC1274C