





## PRODUCTS - POWERFULL OPEN - POWERFULL M - 30 to 80 kva



Standard Electricity Generator - POWERFULL series M version with PERKINS Diesel Engine water-cooled 1500 rpm - 50 Hz and MARELLI Alternator at 400/230 Volt - three-phases with neutral

Mod.	Power				Engine	Alternator
	P.R.P.		L.T.P.			
	kVA	kW	kVA	kW		
 P 30 M	30,00	24,00	33,00	26,40	1103A-33G	MJB160MB4
P 41 M	42,00	33,60	46,00	36,80	1103A-33TG1	MJB200SA4
P 65 M	60,00	48,00	66,00	52,80	1103A-33TG2	MJB200MA4
 P 80 M	80,00	64,00	88,00	70,40	1104A-44TG2	MJB225SA4



Standard Electricity Generator - POWERFULL series M version with PERKINS Diesel Engine water-cooled 1500 rpm - 50 Hz and STAMFORD Alternator at 400/230 Volt - three-phases with neutral

Mod.	Power				Engine	Alternator
	P.R.P.		L.T.P.			
	kVA	kW	kVA	kW		
 P 30 M	30,00	24,00	33,00	26,40	1103A-33G	PI144G
P 41 M	40,00	32,00	45,00	36,00	1103A-33TG1	PI144J
P 65 M	60,00	48,00	63,00	50,40	1103A-33TG2	UCI224E
 P 80 M	80,00	64,00	88,00	70,40	1104A-44TG2	UCI224G

Standard Electricity Generator - POWERFULL series M version with JOHN DEERE Diesel Engine water-cooled 1500 rpm - 50 Hz and MARELLI Alternator at 400/230 Volt - three-phases with neutral

Mod.	Power				Engine	Alternator
	P.R.P.		L.T.P.			
	kVA	kW	kVA	kW		
 JD 30 M	30,00	24,00	33,00	26,40	3029DF128	MJB160MB4
JD 61 M	60,00	48,00	68,00	54,40	4045TFU70	MJB200MA4
 JD 80 M	80,00	64,00	88,00	70,40	4045TF258	MJB225SA4

Standard Electricity Generator - POWERFULL series M version with JOHN DEERE Diesel Engine water-cooled 1500 rpm - 50 Hz and STAMFORD Alternator at 400/230 Volt - three-phases with neutral

Mod.	Power				Engine	Alternator
	P.R.P.		L.T.P.			
	kVA	kW	kVA	kW		
 JD 30 M	30,00	24,00	33,00	26,40	3029DF128	PI144G
JD 61 M	60,00	48,00	63,00	50,40	4045TFU70	UCI224E
 JD 80 M	80,00	64,00	88,00	70,40	4045TF258	UCI224G