









PRODUCTS - POWERFULL OPEN - POWERFULL M - 400 to 650 kva


Standard Electricity Generator - POWERFULL series M version with PERKINS Diesel Engine water-cooled 1500 rpm - 50 Hz and MARELLI Alternator at 400/230 Volt - three-phases with neutral

Mod.	Power				Engine	Alternator
	P.R.P.		L.T.P.			
	kVA	kW	kVA	kW		
 P 450 M	450,00	360,00	495,00	396,00	2506C-E15TAG1	MJB315MB4
 P 500 M	500,00	400,00	550,00	440,00	2506C-E15TAG2	MJB355SA4
 P 600 M	591,00	472,80	650,00	520,00	2806C-E18TAG1A	MJB355MA4
 P 650 M	650,00	520,00	700,00	560,00	2806A-E18TAG2	MJB355MA4


Standard Electricity Generator - POWERFULL series M version with PERKINS Diesel Engine water-cooled 1500 rpm - 50 Hz and STAMFORD Alternator at 400/230 Volt - three-phases with neutral

Mod.	Power				Engine	Alternator
	P.R.P.		L.T.P.			
	kVA	kW	kVA	kW		
 P 450 M	455,00	364,00	500,00	400,00	2506C-E15TAG1	HCI5C
 P 500 M	500,00	400,00	520,00	416,00	2506C-E15TAG2	HCI5C
 P 600 M	591,00	472,80	650,00	520,00	2806C-E18TAG1A	HCI5E
 P 650 M	650,00	520,00	700,00	560,00	2806A-E18TAG2	HCI5F

Standard Electricity Generator - POWERFULL series M version with JOHN DEERE Diesel Engine water-cooled 1500 rpm - 50 Hz and MARELLI Alternator at 400/230 Volt - three-phases with neutral

Mod.	Power				Engine	Alternator
	P.R.P.		L.T.P.			
	kVA	kW	kVA	kW		
 JD 400 M	388,00	310,40	429,00	343,20	6125HF070	MJB315MA4

Standard Electricity Generator - POWERFULL series M version with JOHN DEERE Diesel Engine water-cooled 1500 rpm - 50 Hz and STAMFORD Alternator at 400/230 Volt - three-phases with neutral

Mod.	Power				Engine	Alternator
	P.R.P.		L.T.P.			
	kVA	kW	kVA	kW		
 JD 400 M	388,00	310,40	429,00	343,20	6125HF070	HCI4F

Standard Electricity Generator - POWERFULL series M version with VOLVO-PENTA Diesel Engine water-cooled 1500 rpm - 50 Hz and MARELLI Alternator at 400/230 Volt - three-phases with neutral

Mod.	Power				Engine	Alternator
	P.R.P.		L.T.P.			
	kVA	kW	kVA	kW		

V 505 M	505,00	404,00	556,00	444,80	TAD1641GE	MJB355SA4
V 570 M	570,00	456,00	625,00	500,00	TAD1642GE	MJB355SB4

Standard Electricity Generator - POWERFULL series M version with VOLVO-PENTA Diesel Engine water-cooled 1500 rpm - 50 Hz and STAMFORD Alternator at 400/230 Volt - three-phases with neutral

Mod.	Power				Engine	Alternator
	P.R.P.		L.T.P.		Mod.	Mod.
	kVA	kW	kVA	kW		
V 505 M	500,00	400,00	520,00	416,00	TAD1641GE	HCI5C
V 570 M	550,00	440,00	590,00	472,00	TAD1642GE	HCI5D